# TWO-POST - DP15

Engineered to perform... Built to last!



Two-Post DP15 is Gold Certified

#### **Engineering Excellence**

Forward's U.S. engineers have over 29 years of combined experience designing automotive lifts for service and repair shops. Forward's philosophy is to own our designs rather than use someone else's off the shelf product.

#### **Product** Integrity

21st century design tools allow us to create, control and validate our designs to ensure maximum performance. Forward lifts are thoroughly tested to meet quality and durability standards. All product families are proof load tested to 1½ times rated capacity and rigorously cycle tested.



Padded shut-off bar to prevent damage caused by lifting a vehicle too high



Powder coat finish; more durable than conventional finishes

Specifications	DP15S	DP15S-2
Capacity	15,000 lbs.	
Rise	88-1/2"	
Minimum Lifting Height	5-3/8"	
Overall Height	14' 7"	16' 7"
Height to Shut-Off	13' 10"	15' 10"
Minimum Ceiling Height	14' 8"	16' 8"
Overall Floor Width	12' 4"	
Inside Column Width	1	17"
Drive Through	1	09"
Minimum Adapter Height	5-3/8"	- 7-3/8"
Stackable Adapter Height (low extension)	10	-3/8"
Stackable Adapter Height (high extension)	15	-3/8"
Voltage/Amps	208/230	v, 20 amps
Motor/Phase	2 H	P/1Ø*

Two heavy-duty Direct-Pull<sup>™</sup> hydraulic cylinders designed to minimize down-time by requiring little maintenance

.

Closed loop hydraulic system - preventing hydraulic contamination

Shown: DP15S 15000 lbs. capacity

High tech gear style arm-restraints allowing quick and easy placement of the lift arms



Lift comes with 5" and 10" truck adapter extensions

\*Optional 3-phase available.

Specifications subject to change without notice or liability



Forward Lift 996 Industrial Drive Madison, IN 47250 Phone: 800.423.1722 Fax: 812.273.7329 www.forwardlift.com Lit# Forward DP15\_2010.04

©2010 Forward Lift, Forward Lift is a brand of R.L. Consolidated, A Dover Company, All rights reserved. Unless otherwise indicated, Forward Lift, R.L. Consolidated, Dover and all other trademarks are property of Dover Corporation and its affiliates.

## FOUR POST CR18 NEW! HEAVY DUTY RUNWAY LIFTS

### 18,000 POUNDS CAPACITY



#### **Engineering Excellence**

Forward's U.S. engineers have over 29 years of combined experience designing automotive lifts for service and repair shops. Forward's philosophy is to own our designs rather than use someone else's off the shelf product.

#### **Product Integrity**

21st century design tools allow us to create, control and validate our designs to ensure maximum performance. Forward lifts are rigorously tested to meet quality and durability standards. All product families are proof load tested to 1½ times rated capacity and rigorously cycle tested.



Four-Post CR18-X is Gold Certified

Engineered to perform... Built to last!

## NEW! Forward CR18 18,000 lbs. capacity runway lifts

Single point latch release system releases all four column locks at one time. The non-skid surface allows a sure grip for tires and a "sure foot" for technicians standing on the lift. Multi-position lock components allow lift to be level at any lock position

Front wheel stops can easily be replaced by optional drive through ramps

All hydraulics and mechanical lifting components are concealed under the runway.

122

Optional internal airline connections allow two rolling bridge jacks to operate at the same time

Self chocking approach ramps engage in the rear when the lift is raised

### **Optional Lift Accessories**

- Bolt-On Alignment Kit
- Turning Radius Gauges
- Internal Air Line Kit
- Drive Through Ramps
- Rolling Bridge Jacks
- 30 gallon Oil Drain Pan
- 3-Phase Motors
- Power Unit Cover



Shown: 9,000 lbs. capacity rolling jack PART # RJ901000BK



Shown: 30 gallon capacity rolling oil drain pan PART # 991564

Received to the second se

Forward Lift 996 Industrial Drive Madison, IN 47250

Shown: Bolt-on alignment kit

PART # CR18AK00BL

Phone: 800.423.1722 Fax: 812.273.7329 www.forwardlift.com

Specifications	CR18
specifications	CR18-3
Max. Wheelbase	194" (4928mm)
Wax. Wheelbase	230" (5842mm)
Rise	68" (1727mm)
	22' 11 3/16"
Length Overall	(6990mm)
C	25' 11 3/16" (7904mm)
Width Overall	11' 5 3/4" (3499mm)
Inside of Columns	
Inside of Columns	121 1/2" (3086mm)
Length Between	212" (5385mm)
Columns	248" (6299mm)
Height of Columns	6' 5 3/4" (1975mm)
Width of Runways	22" (559mm)
Height of Runways	7 1/2" (191mm)
Width Between	43" (1092mm)/
Runways (min./max)	46" (1168mm)
Lifting Capacity	18,000 lbs. (8165kg)
Motor	2 HP
Voltage Single	208v-230v
Phase *	2089-2309
Time of Full Rise	105 seconds
	16' x 27'
Min. Bay Size	(4877 x 8230mm) 16' x 30'
-	10 X 30 (4877 x 9144mm)
* 0 * 10 1 1	

 Optional 3-phase electrical available.
Specifications subject to change without notice or liability

#### Lit# CR18\_2011.08

©2011 Forward Lift, Forward Lift is a brand of Vehicle Service Group, A Dover Company, All rights reserved. Unless otherwise indicated, Forward Lift, Vehicle Service Group, Dover and all other trademarks are property of Dover Corporation and its affiliates.



Shown:

Shown with

Model CR18NO-X

18,000 lbs. capacity

# **FOUR-POST LIFTS**

Engineered to perform... Built to last!



#### **Engineering Excellence**

Forward's U.S. engineers have over 29 years of combined experience designing automotive lifts for service and repair shops. Forward's philosophy is to own our designs rather than use someone else's off the shelf product.

#### **Product Integrity**

21st century design tools allow us to create, control and validate our designs to ensure maximum performance. Forward lifts are rigorously tested to meet quality and durability standards. All product families are proof load tested to 1½ times rated capacity and rigorously cycle tested.



Forward's CR/OR14 Series are Gold Certified


### FORWARD: ENGINEERED TO PERFORM...

- Forward<sup>™</sup> lifts are designed in the United States by U.S. engineers.
- Forward Lift's worldwide manufacturing locations are ISO9001 Quality Systems certified ensuring you the best quality products.



• Most of our lifts are third party certified & labeled by a nationally recognized testing laboratory, ETL to ensure they meet or exceed all applicable ANSI standards.

Look for the gold label.



- Because Forward has been in business for five decades and is a member of the Dover family, we provide you with the stability and product support you demand.
- We have one of the best service networks in the industry which provides professional customer support.
- Forward Lift has been an active member of ALI (Automotive Lift Institute) for over 16 years.



- All Forward products are backed by a strong manufacturers warranty.
- Our parts retrieval system allows for shipment of most parts orders within 24 hours.





Shown: CR14 14,000 lbs. capacity

- CR14 Series
- 14,000 lbs. capacity
- Heavy duty hydraulic cylinder
- Single Point latch release system
- Jack track is standard feature
- 6,000 lbs. capacity rolling bridge jacks optional
- Multi-position latch points in each structural leg
- Drive-thru ramps optional



14,000 lbs. capacity

#### **OR14 Series**

- 14,000 lbs. capacity
- Rear wheel slip plates are standard
- Internal airline standard
- Turntables optional
- 6,000 lbs. rolling bridge jacks optional
- Front work step standard feature

#### Available Options:

- Internal Air Line Kit
- Turning Radius Gauges
- Bolt-on alignment kit
- Rolling Bridge Jacks
- Drive Through Ramps
- Power Unit Cover
  - 3-Phase Motors



SY ET

Shown: CR14-X 14,000 lbs. capacity (shown with optional 6,000 lbs. capacity rolling jacks, optional bolt-on alignment kit and optional runway extension kit.)



### **...BUILT TO LAST.**

Easy access to air operated latch release and power unit controls

Self chocking approach ramps and wheel chocks are supplied standard.

> Durable powder coat finish

All hydraulics and mechanical lifting components are concealed under the runway track

Gold ALI Certification Label

Optional 6,000 lbs. rolling bridge jack

Multi-position lock components allow lift to be level at any lock position

Multi-position lock com-

level at any lock position

ponents allow lift to be

15

Shown: CR14-X 14,000 lbs. capacity (shown with optional 6,000 lbs. capacity rolling bridge jacks.)

1/2" thick steel cable

> New redesigned runway can handle wheelbases up to 212 1/2" and capacities up to 14,000 lbs.

New slip plate allows for four wheel alignments up to 158".



Shown: OR14 14,000 lbs. capacity

Specifications	CR14 CR14-X	CR14 CR14-X	OR14S OR14 OR14EL2
	General Service	14000ARKIT Alignment	Open Front Alignment
Capacity	14,000 lbs.	14,000 lbs.	14,000 lbs.
Maximum Wheelbase	180" 204"	176" 197"	158-1/2" 192-1/2" 212-1/2"
Maximum 2-Wheel Alignment	N/A	161" 183"	153" 188" 208"
Maximum 4-Wheel Alignment	N/A	155" (67" min)	142" 158" 158"
Lifting Height	73-3/4"	75-3/4"	73-3/4"
Overall Length	20'-6" 22'-6"	20'-6" 22'-6"	19'-2" 22' 23'-8"
Overall Width	11'-5-1/4"	11'-5-1/4"	11'-7"
Width Inside Columns	114-1/4"	114-1/4"	117-1/2"
Length between Columns	189-1/4"	189-1/4"	171" 205" 225"
Overall Height	7'-4-3/4"	7'-4-3/4"	7'-11-3/16"
Runway Width	20"	20"	20"
Runway Height	7"	7"	7"
Width Between Runways	43"	43"	43"
Rise Time	65 seconds	65 seconds	65 seconds
Voltage	208/230	208/230	208/230
Motor	2 HP	2 HP	2 HP
Minimum Bay Size	15' X 25' 15' X 27'	15' X 25' 15' X 27'	15' X 23' 15' X 26' 15' X 28'



Specifications subject to change without notice or liability



Forward Lift 996 Industrial Drive Madison, IN 47250 Phone: 800.423.1722 Fax: 812.273.7329 www.forwardlift.com Lit# Forward Four-Post\_2010.2

©2010 Forward Lift, Forward Lift is a brand of R.L. Consolidated, A Dover Company. All rights reserved. Unless otherwise indicated, Forward Lift, R.L. Consolidated, Dover and all other trademarks are property of Dover Corporation and its affiliates.

# **LOW-RISE LIFTS**

#### Features

- 10,000 lbs. capacity or 7,000 lbs. capacity
- Drive-over ramps and side rails provide the width to support wider vehicles during approach
- Dual lifting cylinders provide the power required to lift a 10,000 lbs. vehicle
- The TL10 comes with four 3-position adapters, four 3" rubber blocks and four 1-1/2" rubber blocks for added height.



• The TL07 comes with four 3" rubber blocks and four 1-1/2" rubber blocks.









Shown:	TL	1011100	0
10,000 1	lbs.	capacity	

lbs.
"
"
"
"
"
"
"
"
"
"
"
onds

Specifications subject to change without notice or liability.



Forward Lift 996 Industrial Drive Madison, IN 47250 Phone: 800.423.1722 Fax: 812.273.7329 www.forwardlift.com



Lit# Forward Low&Mid-Rise\_2011.07

©2011 Vehicle Service Group<sup>54</sup> Printed in the U.S.A. All rights reserved. Unless otherwise indicated, Forward Lift, Vehicle Service Group<sup>54</sup>, Dover and all other trademarks are property of Dover Corporation and its affiliates.

## **MID-RISE LIFT**

### Engineered to perform... Built to last!

The mid-rise lift is an excellent choice for low ceilings or adding a bay for seasonal increases in business. Provides good working height for tires, brakes and body repairs.

> Shown: 6000 MRL 6,000 lbs. capacity

#### **Engineering Excellence**

Forward's U.S. engineers have over 29 years of combined experience designing automotive lifts for service and repair shops. Forward's philosophy is to own our designs rather than use someone else's off the shelf product.

#### **Product Integrity**

21st century design tools allow us to create, control and validate our designs to ensure maximum performance. Forward lifts are thoroughly tested to meet quality and durability standards. All product families are proof load tested to 1½ times rated capacity and rigorously cycle tested.

#### Model 6000MRL

- Full 6,000 lbs. capacity
- Portable, easy to move
- Two hydraulic cylinders
- Fast operation: 20-30 seconds
- Multiple locking positions
- Truck adapters included

Specifications	6000MRL	
Capacity	6,000 lbs. (2722kg)	
Rise	52"	
Length	83"	
Width	41"	
Fully Lowered	5"	
Motor	110 volt or 220 volt	
Shipping Weight	1,000 lbs. (454kg)	
Specifications subject to change		

# **LOW-RISE LIFTS**

#### Features

- 10,000 lbs. capacity or 7,000 lbs. capacity
- Drive-over ramps and side rails provide the width to support wider vehicles during approach
- Dual lifting cylinders provide the power required to lift a 10,000 lbs. vehicle
- The TL10 comes with four 3-position adapters, four 3" rubber blocks and four 1-1/2" rubber blocks for added height.



• The TL07 comes with four 3" rubber blocks and four 1-1/2" rubber blocks.









Shown:	TL	1011100	0
10,000 1	lbs.	capacity	

lbs.
"
"
"
"
"
"
"
"
"
"
"
onds

Specifications subject to change without notice or liability.



Forward Lift 996 Industrial Drive Madison, IN 47250 Phone: 800.423.1722 Fax: 812.273.7329 www.forwardlift.com



Lit# Forward Low&Mid-Rise\_2011.07

©2011 Vehicle Service Group<sup>54</sup> Printed in the U.S.A. All rights reserved. Unless otherwise indicated, Forward Lift, Vehicle Service Group<sup>54</sup>, Dover and all other trademarks are property of Dover Corporation and its affiliates.